

DIVUS VoIP Server

DIVUS-VS1

embedded box PC

Technical Data:	DIVUS-VS1
Type of design	Ultra compact embedded box PC with Asterisk based PBX software for small intercom applications
Software	
Operating System	Linux with preconfigured Asterisk based PBX software designed for: <ul style="list-style-type: none">- Max. 15 concurrent calls- Max. 10 Intercom external units- Max. 20 Intercom internal units If your project should exceed these limits, options with more performance are available on request. Please ask for your customized solution. Optimized to work only with DIVUS Building Automation products
General characteristics	
Processor	fanless low consumption CPU
Free expansion slots	n/a
Power Supply	7-20 VDC / 100-240 VAC fanless external
Power consumption	max. 6 Watt
Guarantee	24 Months*
Drives	
Storage medium	Compact flash card
Interfaces	
LAN/Ethernet	2 x 10/100 Mbit/s (ext)
USB (Universal Serial Bus)	2 x USB 2.0 (ext)
Serial Interface	1 x RS232 (ext)
Video	no graphic interface, only remote access
Ambient Conditions	
Vibration/Shock resistance	15G / 50G
EMC	EN 55011, 55022, 500081
Temperature	+0°C to +35°C max.
Relative humidity	5% to 80% at 25°C (no humidity/condense)
Authorization	CE
Dimensions	
Outside dimensions	158 x 155 x 28 mm

*warranty ex works, normally 24 months, fixed at order. All data refer on print date, errors and changes excepted.

NOTE: Internal connections are intended as inside the box unit, normally on pin header, external ones as outside the box.

